

Additional equipment *(continued)*

Key: ● Standard ▲ Optional or special See your John Deere dealer for further information.

644 724 Electrical *(continued)*

- ▲ ▲ AM/FM/Weather-Band (WB) radio with CD player
- ▲ ▲ 24- to 12-volt, 15-amp converter
- ● 24- to 12-volt, 8-amp converter

Operator's Station

- ● Quiet Cab with air conditioning/heater
- ● Keyless start with multiple security modes
- ● Sealed-switch module with function indicators
- ● Seat with backrest extension, deep foam, fabric cover, and adjustable air suspension
- ● Hydraulic controls integrated to seat
- ● Seat belt, 76 mm (3 in.), with retractor
- ● Cup holders (2)
- ● Lunch-box/cooler holder
- ● Dome and reading light
- ● 12-volt power port
- ● Rubber floor mat
- ● Tilt steering column
- ● Operator's manual storage compartment
- ● Outside (2) and inside (1) rearview mirrors
- ● Left-side operator-station access
- ● Slip-resistant steps and ergonomic handholds
- ● Sun visor
- ● Front and rear intermittent windshield wiper and washers
- ▲ ▲ Beacon bracket
- ▲ ▲ Rear camera
- ▲ ▲ Rear camera with radar object-detection system
- ● LOADRITE™ L2180™ Payload Scale Ready

Loader Linkage

- ● Z-Bar loader linkage
- ▲ ▲ High-lift Z-Bar loader linkage

Buckets and Attachments

- ● Full line of Deere pin-on buckets
- ▲ ▲ Hi-Vis hydraulic coupler which accepts Euro-pattern attachments (Volvo)
- ▲ ▲ Full line of Deere hook-on buckets and forks

644 724 Overall Vehicle

- ● JDLink™ Ultimate wireless communication system (available in specific countries; see your dealer for details)
- ● NeverGrease™ rear-axle oscillation
- ▲ ▲ NeverGrease steering cylinders
- ● Front and rear tie-downs
- ● Rear cast bumper with rear hitch and locking pin
- ● Articulation locking bar
- ● Loader boom service locking bar
- ● 40-deg. steering articulation to each side with rubber-cushion stops on frame
- ● Vandal protection with lockable engine enclosures, right counterweight storage, battery box, and filler access for radiator/fuel/hydraulic transmission
 - ● Right and left platforms with handrails
- ● Left-side service steps and handholds
- ▲ ▲ Right-side service steps and handholds
- ● Storage compartment
- ● Fuel-tank fill strainer
- ● Heavy-duty fuel-tank guard
- ● Ground-level fueling
- ● Same-side ground-level daily servicing
- ● Michelin 23.5 R 25, 1 Star L-3 tires on 3-piece rims
- ● Environmental drains for engine, transmission, hydraulic oils, and engine coolant
- ▲ ▲ Quick fluid service (engine, transmission, hydraulic oils, and engine coolant)
- ● Fluid-sampling ports for engine, transmission, hydraulic and axle oils, and engine coolant
- ● Fenders, front
- ▲ ▲ Fender, full-coverage, front
- ▲ ▲ Fenders, full-coverage, front and rear
- ▲ ▲ Transmission side-frame guards
- ▲ ▲ Bottom guards, front frame and transmission
- ▲ ▲ Lift eyes

While general information, pictures, and descriptions are provided, some illustrations and text may include product options and accessories NOT AVAILABLE in all regions, and in some countries products and accessories may require modifications or additions to ensure compliance with the local regulations of those countries.

Actual machine configuration may differ from image. Not all models available in all countries.

Net engine power is with standard equipment including air cleaner, exhaust system, alternator, and cooling fan at test conditions per ISO 9249. No derating is required up to 3050-m (10,000 ft.) altitude. Specifications and design subject to change without notice. Specifications with the exception of bucket capacity are in accordance with all applicable ISO standards. Except where otherwise noted, these specifications are based on units with applicable linkage and standard equipment, ROPS cab, rear cast bumper/counterweight, transmission side-frame guards, bottom guards, standard tires, full fuel tank, and 79-kg (175 lb.) operator.