

UNROLLA LX105

THE MOUNTED ROUND BALE UNROLLERS

Easier to use than any other type chain feeders on the market today. Being the most innovative, with 6 unique features you won't find on any other bale feeder that makes it easier to use, more versatile, and saves your precious time. Recommended for farms feeding 50-800 bales each year, the self-loading 3-point linkage mounted feeder is suitable for feeding out all but the tightest of round bales and baled silage, loose silage, maize, fodder-beet and more.

DUAL SIDE FEED

A single lever control enables the LX105 to feed bales out to the left or right and gives precise control of the rate of feed.

LOW-MAINTENANCE BEARINGS

The LX105 is equipped with our proven, greasable, self-aligning bearings with trash shields that will easily outlast any type of bush system.

TOUGHEST CHAIN

Zinc-plated 12,000 lb chains with heavy duty rollers and pins make our chain drive system almost twice as strong as others. The greater wear surface on each roller increases chain life because they can't stretch or snake. Fully enclosed chain and sprocket guides eliminate derailment.

BALE CHAMBER

Even the stickiest bales are not a problem for our new bale chamber. It is steeper and deeper for feeding out a larger variety of bales and preventing roll out on steep terrain. Increased front and rear bale chamber enclosure reduces feed falling out, and a high security bar holds the bale securely in the chamber.



SNAPLOX AUTO-LATCH SYSTEM

The clever Snaplox auto-latch system saves you the time and hassle of opening the tractor's back window and tugging a rope to unlatch the cradle. Uneven ground does not affect it as the feet will still push up enough to unlatch.

CONNECT EITHER END

To simplify loading and connecting, we've allowed you to connect or load from either end of the cradle. This also allows operators to switch the direction the bale is being unrolled without unloading the bale, which makes feeding tighter bales on both sides of the passage in single-access barns much quicker and easier.

TEETH

Our unique, extra-strong 5 cm shark teeth are designed to prevent feed being dragged under the feeder by releasing it at precisely the right moment. Teeth can be angled for more aggression, or the whole bar can be unbolted or removed without breaking the chain or using a grinder.

COVERED DRIVE SHAFTS

The covers keep the bearings clean and ensure longer bearing life, reducing maintenance and downtime.

FLOOR

Fully enclosed floor design extends over the drive shafts, protecting them from wrapping, and eliminates wastage by preventing feed from falling out. Made from solid, 45 mm polyethylene, it is UV and shock resistant, and will not rust or corrode.

Its extra slipperiness reduces the amount of torque needed and makes it easier to turn bales that would otherwise grip to a steel surface.

SPECIFICATIONS

BALE SIZES ROUND: Up to 5' x 6'
BALE SIZES SQUARE: Up to 3' x 4' x 7'
(requires optional rail/roller kit)
BALE WEIGHT: Up to 1250 kg
UNIT WEIGHT: 480 kg

CAPACITY: 1 bale
LENGTH: 2071 mm
WIDTH: 2055 mm
HEIGHT: 1051 mm

LOADING: Patented Snaplox self-loading system
HYDRAULICS REQUIRED: 1x double-acting (30-60 L/mm), 2250-3000 psi
TYNES: 2 x forged high-tensile

HUSTLER®

UNROLLA LX105

