

AUTO-RESET CHISEL CULTIVATORS

KON Semi-Chisel cultivators with 40x30mm tines provide high vibration effect for shallow to deep working of the soil from 50mm up to 300mm depth. Ideal for primary and secondary cultivation in stony and compacted soil to improve penetration of water and to aerate the soil. At the same time they mix stubble and residue for faster decomposition preparing the soil for re-seeding.



KON SEMI-CHISEL (3.3m)
2 x row fixed frame
with rear roller



KON SEMI-CHISEL
SCH-3FH17 (4.8m)
17 Tine Hydraulic folding
with optional rear roller,
wheels and lights



SEMI CHISEL 40x30

2.8m to 5.6m
working widths

MODEL : KON SEMI-CHISEL 40x30 Shank 2 X ROWS

MODEL	Work/Transport Width	No. Tines	Tine Spacing	Max Depth	Frame Dimensions	Frame Clearance	HP Min/Max	*Weight
Fixed Frame								
SCH-2FH11	2.8m/3.1m	11	250mm	300mm	100x100x8mm	700mm	80/150	1000kg*
SCH-2FH13	3.3m/3.6m	13	250mm	300mm	100x100x8mm	700mm	90/150	1150Kg*
SCH-2FH15	3.8m/4.1m	15	250mm	300mm	100x100x8mm	700mm	100/150	1300Kg*
Hydraulic Folding Frame								
SCH-2FH15*	3.8m/2.8m	15	250mm	300mm	100x100x8mm	700mm	100/150	1550Kg*
SCH-2FH17*	4.3m/2.8m	17	250mm	300mm	100x100x8mm	700mm	110/150	1650Kg*
SCH-2FH19*	4.8m/2.8m	19	250mm	300mm	100x100x8mm	700mm	120/150	1800kg*

MODEL : KON SEMI-CHISEL 40x30 Shank 3 X ROWS

MODEL	Work/Transport Width	No. Tines	Tine Spacing	Max Depth	Frame Dimensions	Frame Clearance	HP Min/Max	*Weight
Fixed Frame								
SCH-3FH11	2.8m/3.1m	11	250mm	300mm	100x100x8mm	700mm	80/170	1120Kg*
SCH-3FH13	3.3m/3.6m	13	250mm	300mm	100x100x8mm	700mm	90/170	1270Kg*
SCH-3FH15	3.8m/4.1m	15	250mm	300mm	100x100x8mm	700mm	100/130	1420Kg*
Hydraulic Folding Frame								
SCH-3FH17*	4.3m/2.8m	17	250mm	300mm	100x100x8mm	700mm	110/170	2350Kg*
SCH-3FH19*	4.8m/2.8m	19	250mm	300mm	100x100x8mm	700mm	120/170	2640Kg*
SCH-3FH22*	5.6M/2.8m	22	250mm	300mm	100x100x8mm	700mm	150/170	3400Kg*

*Note: All Weights are with Rear Roller: (H) = Hydraulic Folding Frame



STANDARD FEATURES

- Compact 3-point linkage for close mounting to tractor - better weight distribution
- Auto-Reset pre-tensioned coil springs providing soil vibration and obstacle protection
- High quality European spring tines and points for longer life
- 2 x row and 3 x row tine options. Fixed or hydraulic folding frame



OPTIONS

- Rear flat bar cage roller
- Front depth control wheels (pair)
- HD Levelling tine bar 1 x row (between tines and roller)
- Double rear spring tine bar 2 x rows - for increased soil working and levelling



Rear flat bar roller with double spring tine bar 2 x rows



Rear flat bar roller and HD levelling tine bar

YOUR LOCAL DEALER IS:

Proudly Imported and Distributed by



Your Farm Equipment Co-operative

www.originagroup.co.nz

PO Box 673 Cambridge 3450
 57 Hautapu Road, Cambridge, New Zealand
 Ph: +64 7 823 7582 Fax: +64 7 823 7583
 Email: info@originagroup.co.nz

DISCLAIMER: This publication is intended to provide reasonable information relating to the subject matter contained herein. However specifications and product designs are subject to change without prior notice therefore no liability for damages in respect of or arising out of this information will be accepted. Please check that the information contained is current at time of purchase.