













It's easy to take control

Electrohydraulic (EH) ISO-pattern joystick controls that allow customized machine operations based on operator preference are standard on the 316GR.

Elevated by design

Radial-lift boom provides generous reach at mid-range lift heights and enables the 316GR to excel at digging, grading, and backfilling applications.

Try it on for size

Weighing only 6,180 pounds, this compact is easy to trailer behind a standard pickup truck using the convenient front and rear tie-downs. Heavy-duty tire option slims the 316GR down to a narrow 60-inch width.

Imagine the possibilities

Ample axle torque and optimized boom and bucket breakout forces help carve out clay, push through piles, and heap the load.

Step up the pace

Two-speed transmission option provides faster transport speeds of up to 10 miles per hour, to move around the jobsite quicker and push productivity even further.

Packed for productivity

Low center of gravity, 30-degree bucket rollback, optional ride control, and optional hydraulic self-leveling help keep forks loaded and buckets full. Add capacity with up to two sets of rear counterweights.

Big ideas that deliver

Large cab entryway with swing-out door, generous foot- and legroom, sealing and pressurization to minimize dust and noise, and adjustable high-back sculpted seat optimize operator comfort. Overhead panel conveniently puts machine data on the left and control switches on the right. Easy-to-read LCD monitor reveals a wealth of vital operating info and advanced diagnostics.

Seeing is believing

Clear sightlines to the cutting edge and bucket corners, above and below the lift arms, and the jobsite ahead and behind instill confidence in close quarters. Optional LED side lighting and rearview camera further enhance visibility.

Tackle the to-do list

Swing-out rear door enables easy, ground-level access to daily service checkpoints and cooling system components. Neat freaks and rental yards can appreciate the convenient cab-footwell access that helps speed cleaning.

Work your connections

Equip your skid steer with your choice of over 100 available John Deere attachments to expand the flexibility of your operation. Increased auxiliary hydraulic flow and power compared to previous models boosts attachment performance. Add a snow blower, snow pusher, or angle broom to make quick work of winter's white stuff.



316GR SKID STEER





Safety first

Standard personal-protection features include in-cabactivated boom lock and triple-interlock system that detects the presence of the operator to help keep harm's way at bay.

Remote diagnostics and support

To maximize uptime and lower costs, JDLink™ connectivity provides machine location, utilization data, and alerts to help you maximize productivity and efficiency. JDLink also enables John Deere Connected Support™. Dealers use Expert Alerts based on data from thousands of connected machines to proactively address conditions that may otherwise likely lead to downtime. Your dealer can also monitor machine health and leverage remote diagnostics and programming capability to further diagnose problems and even update machine software without a time-consuming trip to the jobsite.*

 $\mbox{\ensuremath{^{\star}}}\mbox{\ensuremath{^{Availability}}}\mbox{\ensuremath{^{availability}}}\mbox{\ensuremath{^{c}}}\mbox{$

316GR SKID STEER SPECIFICATIONS

Engine	316GR		
Engine Manufacturer and Model	Yanmar 4TNV86CHT	Displacement	2.1 L (128 cu. in.)
		Rated Engine Speed	
Non-Road Emission Standard	EPA Final Tier 4/EU Stage IV		2,600 rpm
Cylinders	4 (5 C LW (63 b =) = t 3 C 0 0 == ==	Torque Rise	21% at 1,690 rpm
Net Power (SAE J1349 / ISO 9249)	45.6 kW (61 hp) at 2,600 rpm	Aspiration	Turbocharged
Gross Rated Power (ISO 14396)	48.5 kW (65 hp) at 2,600 rpm	Air Cleaner	Dry dual element
Peak Torque	207 Nm (153 ftlb.) at 1,690 rpm		
Cooling			
Fan Type	Direct belt drive		
Powertrain		(=1)	
Туре	Hydrostatic-manual or electrohydrauli	c (EH); 4 – 80 heavy-duty (HD) cont	inuous-loop chain
Speeds			
Single	11.1 km/h (6.9 mph)		
2 Speed, High	16.3 km/h (10.1 mph)		
Axles	Induction-hardened, 1-piece forged axle	e shafts with maintenance-free oil-b	ath lubrication of inner and outer axle bearings
Maximum Axle Torque	6459 Nm (4,764 lbft.)		
Tractive Effort	3552 kgf (7,831 lbf)		
Final Drive	High-strength, adjustment-free chains	5	
Brakes	Integral, automatic, spring-applied, hy		rake
Hydraulics	gran, carameter, spring applied, hy		
Pump Flow, Standard	63 L/m (17 gpm)		
System Pressure at Couplers	23 787 kPa (3,450 psi)		
Hydraulic Horsepower Flow (calculated),	25 kW (33 hp)		
Standard	25 KW (55 Hp)		
Auxiliary Hydraulics	Optional connect-under-pressure with	flat faced couplers	
	Optional connect-under-pressure with	That-raced couplers	
Cylinders	John Doore host treated shrome plate	ad palishad sulindar rade bardanad	stool (roplaceable bushings) pivot pins
Type Electrical	John Deere heat-treated, Chrome-plati	ed polistied cyllider rods, flarderied	steel (replaceable bushings) pivot pins
	12 volt		
Voltage			
Battery Capacity	750 CCA standard / 925 CCA with optic		
Alternator Rating	70 amp with no air conditioning (A/C)	/ 90 amp with A/C	
Lights			
Standard	Halogen: 2 front and 1 rear		
Deluxe	LED: 2 front, 2 side, and 1 rear		
Operator's Station			
ROPS (ISO 3471) / FOPS (ISO 3449) structur	e with quick pivot standard		
Tires/Wheels			-:::::
Standard Tire Size	10 x 16.5	_ ′	
Serviceability			
Refill Capacity			
Fuel Tank	71 L (19 gal.)		T
Operating Weight			
Base Machine	2806 kg (6,180 lb.)		
Machine Dimensions			
Length Without Bucket	2.63 m (103.0 in.) (8 ft. 7 in.)		
3 Length With Foundry Bucket	3.24 m (127.6 in.) (10 ft. 8 in.)		
C Width Without Bucket	1.60 m (62.9 in.) (5 ft. 3 in.)		
D Height to Top of ROPS	1.96 m (77.2 in.) (6 ft. 5 in.)		H
E Height to Hinge Pin	2.92 m (115.1 in.) (9 ft. 7 in.)		Α
F Dump Height With Foundry Bucket	2.25 m (88.6 in.) (7 ft. 5 in.)		
G Dump Reach	2.23 III (00.0 III.) (7 I L. 3 III.)		В
	0.40 m (15.8 in.)	K	
With Construction Burket			
With Construction Bucket	0.58 m (22.8 in.)		
• Wheelbase	1.05 m (41.5 in.) (3 ft. 5 in.)		
Ground Clearance	0.18 m (7.0 in.)		7
I Angle of Departure	22.3 deg.		
Front Turn Radius With Foundry Bucket	2.01 m (79.0 in.) (6 ft. 7 in.)	_	
Dump Angle (full lift height)	45 deg.		+ [
• B	20 dag		
M Bucket Rollback (ground level)	30 deg.		i i
M Bucket Rollback (ground level)	ou deg.		
M Bucket Rollback (ground level)	50 deg.		

While general information, pictures, and descriptions are provided, some illustrations and text may include product options and accessories NOT AVAILABLE in all regions, and in some countries products and accessories may require modifications or additions to ensure compliance with the local regulations of those countries.

Loader Performance	316GR		
Tipping Load	1589 kg (3,500 lb.)	Boom Breakout Force (continued)	
SAE Rated Operating Capacity	795 kg (1,750 lb.)	With Construction Bucket	2043 kg (4,500 lb.)
With Counterweight	863 kg (1,900 lb.)	Bucket Breakout Force	
Boom Breakout Force		With Foundry Bucket	2384 kg (5,250 lb.)
With Foundry Bucket	2157 kg (4,750 lb.)	With Construction Bucket	1816 kg (4,000 lb.)

Additional equipment

Key: ● Standard ▲ Optional or special

See your John Deere dealer for further information.

316GR	Engine
•	Meets EPA Final Tier 4/EU Stage IV emissions
	Yanmar 4TNV86CHT
•	Auto-idle
•	Automatic preheat
•	Electronic injection system
A	Engine air precleaner kit
	Fuel tank, 71 L (19 gal.)
•	John Deere COOL-GARD™ II Extended-Life
	Engine Coolant
	John Deere Plus-50™ II 0W40 initial engine oil fill*
•	4-cylinder 48.5 kW (65 gross hp)/ 45.6 kW
	(61 net hp), 2.1-L (128 cu. in.) displacement
•	5-micron primary fuel filter and water separator
A	Cold-weather starting package with 925-CCA
	battery
	Cooling System
•	Coolant overflow bottle recovery tank
	Direct belt-drive cooling fan system
•	No-tools-required swing-out oil cooler
	Powertrain
	High-strength adjustment-free final-drive
	chains
•	Automatic spring-applied hydraulically released wet-disc park brake
•	Transmission, single speed
Ā	Transmission, 2 speed
	Hydraulic System
•	John Deere heat-treated, chrome-plated
_	cylinder rods with replaceable bushings
	Connect-under-pressure auxiliary couplers
•	Quick-check hydraulic fluid-level sight glass
•	1,000-hour, 5-micron hydraulic filter
•	Axial-piston hydrostatic pump
	Electrical
	Automatic engine/hydraulic shutdown

protection system

Courtesy lighting

Auxiliary hydraulics operator-presence system

316GR Electrical (continued) Deluxe instrumentation EMU with: Operatorselectable monitoring - Hour meter, engine rpm, battery voltage, diagnostics, EMU configuration, engine coolant temperature, hydraulic oil temperature / LED warning indicators - Glow pluq, seat switch, seat belt, door open, auxiliary hydraulics, park brake engaged, 2-speed engaged, stop, low engine oil pressure, engine coolant over-temperature, battery not charging, air filter restriction, hydraulic filter restriction Deluxe LED lighting package with additional side lights (2), front lights (2), and rear light (1) Front and rear halogen work lights Triple-interlock operator-presence control system Backup alarm Battery, 750 CCA Horn Operator's Station Deluxe cab headliner Keyless-start sealed-switch module with integrated anti-theft system Pull-down adjustable lap bar Quick-pivot ROPS Rear window Top window Removable top window Vinyl cab enclosure Glass cab enclosure Sliding/locking/removable glass side windows ROPS/FOPS operator structure Seat belt, 51-mm (2-in.), retractable Seat belt, 76-mm (3-in.), retractable Shoulder belt Water-shedding deluxe vinyl seat Air-ride cloth, heated seat

316GR	Operator's Station (continued)
	12-volt power port / Dome light / Cargo
	storage / Beverage holder
	Air conditioning with heater/defroster
A	AM/FM radio with Bluetooth® for audio streaming
•	Electrohydraulic (EH) ISO-pattern joystick controls
A	EH joystick performance package: Switchable ISO-H pattern / Creeper mode / Boom/bucket speed settings / Adjustable propel settings / Attachment controls
A	Floor mat with left footrest
•	Rearview mirror
	Boom-mounted side mirrors
A	Rearview camera
	Loader
•	In-cab boom lockout to secure loader before exiting seat
•	John Deere Quik-Tatch™
	Power Quik-Tatch
	John Deere radial-lift boom
	Hydraulic self-leveling on/off
	Ride control
	Other
•	Convenient front (1) and rear (2) tie-downs
	Environmental drains for all fluid reservoirs
A	10 x 16.5 10 PR Galaxy "Beefy Baby III" heavy-duty (HD) tires for 1.52-m (60 in.) machine width
A	Tire options: SKS Xtra Wall, Galaxy Beefy Baby III, Galaxy Hulk, and Brawler Solid-Flex
	Chrome exhaust stack
	Rear counterweights (2), 45.36 kg (100 lb.)
A	Single-point lift kit
	SMV sign kit
•	JDLink™ wireless communication system (available in specific countries; see your

dealer for details)

*500-hour engine oil-change intervals when John Deere Plus-50 II oil and John Deere oil filter are used.

Air-ride vinyl seat



